

Identification of Material and Supplier

Product Names

Generic: Jutemaster® Thick Mat, Jutemaster® Thick Mat Plus,
Jutemaster® FM, JuteTreeMat

Recommended Uses

Ground cover used for preventing erosion and for promoting selective plant growth and stability.

Supplier Details and Contact Information

Supplier: UNITED BONDED FIBRES PTY LTD.
Address: 50 Bakers Road, Coburg North, VIC 3058.
Telephone (in Aust): 1800 554 424
Facsimile: 1800 653 650
Email: customercare@unitedbonded.com.au
Websites: www.unitedbonded.com.au

Health Hazard Information

Health Effects: No known physical or health hazards associated with these products.
Swallowed/Eye/Skin/Inhaled: No toxic reactions have been reported which can be attributed to these products over many years of experience in our plants and customer operations.

First Aid

Swallowed/Eye/Skin/Inhaled: Not Applicable.
Advice to Doctors: Not Applicable.

Precautions for Use

Exposure Limits: None Specified.
Ventilation: No special requirements.
Personal Protection: No special requirements.
Flammability: Do not expose to direct flame, welding, grinding or other incendiary sparks as product is combustible. Care must be taken to avoid such exposure.

Safe Handling Information

Storage and Transport: Requirements as noted above.
Disposal: Not applicable.
Fire/Explosion Hazard: Relatively low flame response. Will not explode. Use any fire fighting extinguishant. Like most organic materials gives off CO, CO₂, and H₂O during combustion.

Fire Fighting Measures

This material has limited flammability properties but will burn if exposed to direct flame. Any plastic packaging may also decompose or burn when exposed to direct flame. If subject to fire evacuate the area and contact emergency services. Use water fog to cool affected product and packs.

Transportation Information

Manufacturer's Code:	Internal Codes are not used externally.
Un Number:	None Allocated.
Dangerous Goods Class:	None Allocated.
Hazchem Code:	None Allocated.
Subsidiary Risk:	None Allocated.

Regulatory Information

Classified as NON-HAZARDOUS according to ASCC/NOHSC criteria.

Poisons Schedule:	None Allocated.
--------------------------	-----------------

Physical Description and Properties

Appearance:	Light brown needled felt with scrim support.
Melting Point:	Not applicable.
Vapour Pressure:	Not applicable.
Per Cent Volatiles:	Nil.
Specific Gravity:	1.3
Flash Point:	Not applicable.
Ingredients:	Natural jute fibre from the jute plant.
Chemical Entity:	Jute plant consisting of cellulose.

FOR FURTHER INFORMATION OR AN MSDS, CALL 1800 554 424 OR E-MAIL customer@unitedbonded.com.au

This MSDS is issued by United Bonded Fabrics in accordance with Worksafe Australia Guidelines. The information must not be altered, added to or deleted. United Bonded Fabrics will issue a new MSDS whenever a change occurs in product specification, information about the product, or Worksafe Guidelines. United Bonded Fabrics will not accept responsibility for any loss or damage caused by changes in content of the MSDS made by any other person or organisation. This information is provided in good faith and to the best of United Bonded Fabrics knowledge, was accurate at the time of preparation. No responsibility can be accepted for any errors or omissions. Users should decide for themselves as to the suitability of this information for their particular purposes or specific circumstances. Since information contained in this document may be applied under conditions beyond United Bonded Fabrics control, no responsibility can be accepted by United Bonded Fabrics for any loss or damage caused by any person acting or refraining from actions as a result of this information.
© Copyright 2009. ® and ™ are trademarks used by United Bonded Fabrics.

50 Bakers Road Coburg North VIC 3058
Telephone: 1800 554 424 • Fax: 1800 653 650
Email: customer@unitedbonded.com.au
Website: www.unitedbonded.com.au